



FULLY AUTOMATIC RANDOM FOUR EDGE SEALER

CT4E COMPARISON

CHART



WANT TO KNOW MORE ABOUT THIS MACHINE?

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

## **STANDARD MODEL INFORMATION:**

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE LENGTH (min max.) x WIOTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING Weight (LBS)	POWER Requirements	AIR REQUIREMENTS
CT4EL22-3 3" Tape Head Left Side Infeed	(94.6") x (61.5") x (70.5")	(11.81" - 23.62") × (9.84" - 23.62") × (9.84" - 23.62")	Determined at the time of order	Up to 5	1,470	110 Volts 60 Hz	100 PSI, 10+ SCFM

MODEL	MACHINE DIMENSIONS  LENGTH x WIDTH x HEIGHT	CARTON RANGE LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER Requirements	AIR REQUIREMENTS
CT4EL22-3 3" Tape Head Left Side Infeed	(94.6") × (61.5") × (70.5")	(11.81" - 23.62") x (9.84" - 23.62") x (9.84" - 23.62")	Determined at the time of order	Up to 5	1,470	110 Volts 60 Hz	100 PSI, 10+ SCFM
CT4ER22-3 3" Tape Head Right Side Infeed	(94.6") x (61.5") x (70.5")	(11.81" - 23.62") x (9.84" - 23.62") x (9.84" - 23.62")	Determined at the time of order	Up to 5	1,470	110 Volts 60 Hz	100 PSI, 10+ SCFM
CT4ES32-3 <b>3" Tape Head</b> Straight Feed	(133.8") x (72.2") x (85.8")	(9.5" - 32.0") x (10.0" - 22.0") x (5.0" - 20.0")	Determined at the time of order	Up to 5	1,675		100 PSI, 10+ SCFM

WWW.BESTPACK.COM VERSION 4.0\_0624