


STAINLESS AUTOMATIC UNIFORM SIDEDRIVE AS-S COMPARISON CHART



**WANT TO KNOW MORE
ABOUT THIS MACHINE?**

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE** LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	POWER REQUIREMENTS	AIR REQUIREMENTS	CARTONS PER MIN. ***
AS22-2S 2" Tape Head	(77.7") x (33.8") x (69.0")	(8.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 57

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE** LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	POWER REQUIREMENTS	AIR REQUIREMENTS	CARTONS PER MIN. ***
AS12-2S 2" Tape Head	(70.2") x (26.5") x (68.0")	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 57
AS12-3S 3" Tape Head	(70.2") x (26.5") x (68.0")	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 34
AS22-2S 2" Tape Head	(77.7") x (33.8") x (69.0")	(8.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 57
AS22-3S 3" Tape Head	(77.7") x (33.8") x (69.0")	(8.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 34

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

* SAFETY GATES ARE AN ADDITIONAL 20" LONG | ** HIGH SPEED | ** OUTSIDE DIMENSIONS ONLY | *** BASED ON CUSTOMER APPLICATION