



# FASTEST

## FULLY AUTOMATIC UNIFORM

### CARTON SEALING SOLUTION




**UNLOCK THE POWER OF DATA**  
REAL-TIME DATA FROM ANYWHERE

## QUICK HIGHLIGHTS

**SEALS UP TO 57 CARTONS PER/MIN.\***

\*SPEED DEPENDENT ON CARTON SIZE AND MACHINE OPTIONS


- Infeed and Outfeed Conveyor Control
- Jam Detection
- Includes our Data Advantage System
  - Realtime Monitoring Dashboard
  - Advanced Performance Analytics/Metrics
  - Increased Productivity and Reduced Downtime



## CARTON RANGE

Specifications based on AS22-2

Length (min. - max.)	Width (min. - max.)	Height (min. - max.)
(8.0" - 27.5)	(6.0" - 20.0")	(5.5" - 20.0")



# AS

## AUTOMATIC UNIFORM SIDEDRIVE

The AS Series from BestPack™ is an automatic carton sealing machine that is ideal for consistent in-line carton sealing processes. It features a sturdy four column support structure and dual motor side belt technology, which enables it to close all four top flaps and seal the top and bottom of the carton. This machine is designed to meet the needs of various carton closure applications.




**FREE PRODUCT SUPPORT:**  
TRAINING VIDEOS | ONLINE MANUALS | TECH SUPPORT

\*CONTACT YOUR LOCAL BESTPACK REPRESENTATIVE FOR MORE INFORMATION

[WWW.BESTPACK.COM](http://WWW.BESTPACK.COM)

VERSION 5.0\_0424



### SIDEBELT DRIVE SYSTEM

Gently pulls product through while reducing less wear & tear on parts.



### DATA ADVANTAGE SYSTEM

Provides real time data to help deal with costly avoidable issues and improve production efficiency.



### ACCESSIBLE TECHNICAL SUPPORT

Convenient technical support is readily available via a QR code on this solution.



### TOP COMPRESSION ROLLERS

Eliminates the carton's top gap for added product security.



### TAPE MONITORING SYSTEM

Low tape, no tape and no cut monitoring system, notifies the user of potential downtime.




### COMPLETE BED ROLLER SYSTEM

Increase through put while reducing strain on the motor.

## MACHINE FOOTPRINT

Specifications based on AS22-2



Note: Dimensions are all subject to change without prior notification.

## OPTIONS

- High-Speed Options
  - VFD Motor Upgrade (150ft per min.)
  - High-Speed Motor Upgrade (125ft per min.)
- Available in Stainless Steel
- Additional Safety Options:
  - Sealing Area Gates
  - Bottom Skirt Guard
  - Exit Gates
  - Safety Relay
- Indexer Option

## POPULAR AS MODELS

PLEASE REFER TO COMPARISON CHART FOR COMPLETE LIST OF MODELS.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE*** LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	POWER REQUIREMENTS	AIR REQUIREMENTS	CARTONS PER MIN. ****
AS12-2H** 2" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 57
AS12-3 3" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 34
AS12-3H** 3" Tape Head	(70.2") x (26.5") x (68.0")*	(8.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 57
AS22-2 2" Tape Head	(77.7") x (33.8") x (69.0")*	(8.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	110 Volts 60 Hz	40-60 PSI, 4-5 SCFM	Up to 34

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

\* SAFETY GATES ARE AN ADDITIONAL 20" LONG | \*\* HIGH SPEED | \*\*\* OUTSIDE DIMENSIONS ONLY | \*\*\*\* BASED ON CUSTOMER APPLICATION



For more information please go to:  
**WWW.BESTPACK.COM** or call us at **1.888.588.2378**