

FULLY AUTOMATIC 4-EDGE WITH STRAIGHT FEED
AT4ES COMPARISON CHART



WANT TO KNOW MORE ABOUT THIS MACHINE?

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
AT4ES22-3 3" Tape Head	(110.3") x (49.8") x (60.5")	(10.3" - 23.5") x (9.8" - 23.5") x (9.8" - 23.5")	Determined at the time of order	Up to 5	1,970	110 Volts 60 Hz	100 PSI, 10+ SCFM

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
AT4ES22-3 3" Tape Head	(110.3") x (49.8") x (60.5")	(10.3" - 23.5") x (9.8" - 23.5") x (9.8" - 23.5")	Determined at the time of order	Up to 5	1,970	110 Volts 60 Hz	100 PSI, 10+ SCFM