




# BG20

**2.0 MIL (50 MICRON) TOTAL TAPE THICKNESS**  
**25 MICRON CAST BOPP LOW ELONGATION FILM**  
**ROHM & HAAS ACRYLIC ADHESIVE**


BG20 is specially formulated for 100% recycled corrugated. By adding better quick tack properties to the benefits of acrylic, BG Tape is a perfect alternative to Hot Melt Tape.



EXTREME TEMPERATURES



GREAT INITIAL TACK



DOESN'T YELLOW TO UV

**2.0 MIL (50 MICRON)\***  
Total Thickness

**19 OZ/INCH WIDTH\*\*\***  
Peel Adhesion

**1.0 MIL (25 MICRON)\***  
Adhesive Thickness


**1.0 MIL (25 MICRON)\***  
Film Thickness

**20 LBS/IN WIDTH\*\***  
Tensile Strength


**110%\*\***  
Elongation % At Break

Test Methods: \* ASTM D-3652; \*\* ASTM D-3759; \*\*\* ASTM D-3330


## AVAILABLE COLORS



## AVAILABLE LENGTHS



## AVAILABLE WIDTHS



## STANDARD FEATURES

- Good Initial Quick Tack
- Specially formulated ROHM & HAAS acrylic adhesive for use in hot & cold temperatures
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Specially formulated 110% elongation low stretch cast film increasing machine length roll performance
- Unlimited Shelf Life
- Available Hand & Machine Length Rolls
- RoHS Compliant
- Tape manufactured in ISO 9001 & 14001 Facilities

### SERVICE TEMPERATURE

Minimum Temp.: **-30°F**  
Maximum Temp.: **200°F**

### USAGE & STORAGE TEMPERATURE

Minimum Temp.: **32°F**  
Maximum Temp.: **150°F**

### IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: **77°F +/- 5°F**  
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.