

FORMULATED FOR

CHALLENGING & DIFFICULT APPLICATIONS

CARTON SEALING TAPE



FORMULATED
FOR RECYCLED CORRUGATE

QUICK HIGHLIGHTS

- Good Initial Quick Tack
- Specially Formulated 110% Elongation Low Stretch Cast Film (Increasing Machine Length Roll Performance)
- UV Light Resistant
- Specially Formulated ROHM & HAAS
- Unlimited Shelf Life
- RoHS Compliant

2.0 MIL (50 MICRON)* Total Thickness	19 oz/inch WIDTH*** Peel Adhesion	1.0 MIL (25 MICRON)* Adhesive Thickness
1.0 MIL (25 MICRON)* Film Thickness	20 LBS/IN WIDTH** Tensile Strength	110%** Elongation % At Break
Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330		

SERVICE TEMPERATURE
Minimum Temp.: -30°F Maximum Temp.: 200°F

USAGE & STORAGE TEMPERATURE
Minimum Temp.: 32°F Maximum Temp.: 150°F

IDEAL STORAGE TEMPERATURE
Ideal Storage Temp.: 77°F +/- 5°F Ideal Storage Humidity: 55% +/- 5%

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.

*Contact Your Local BestPack Representative for More Information

AVAILABLE COLORS:

AVAILABLE LENGTHS: 100m 914m 1372m

AVAILABLE WIDTHS: 48mm 72mm

BG20

**2.0 MIL (50 MICRON) TOTAL TAPE THICKNESS
25 MICRON CAST BOPP LOW ELONGATION FILM
ROHM & HAAS ACRYLIC ADHESIVE**

BG20 is specially formulated for 100% recycled corrugated. By adding better quick tack properties to the benefits of acrylic, BG Tape is a perfect alternative to Hot Melt Tape.



LEARN MORE ABOUT OUR TAPE:
BROCHURES | MATERIAL SAFETY DATA SHEET | ROHS INFORMATION