

BESTPACK'S FLAGSHIP PRESSURE SENSITIVE

ACRYLIC CARTON SEALING TAPE



TEMPERATURE-RESISTANT
WATER-BASED ACRYLIC

QUICK HIGHLIGHTS

- Unlimited Shelf Life
- UV Light Resistant
- Specially Formulated 110% Elongation Low Stretch Cast Film (Increasing Machine Length Roll Performance)
- Specially Formulated ROHM & HAAS (for use in Hot & Cold Temperature)
- RoHS Compliant
- Meets FDA Food Requirements for Indirect Food Contact

2.0 MIL (50 MICRON)* Total Thickness	20 oz/inch WIDTH*** Peel Adhesion	0.9 MIL (22 MICRON)* Adhesive Thickness
1.1 MIL (28 MICRON)* Film Thickness	22 LBS/IN WIDTH** Tensile Strength	110%** Elongation % At Break
Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330		

SERVICE TEMPERATURE
Minimum Temp.: -30°F Maximum Temp.: 200°F

USAGE & STORAGE TEMPERATURE
Minimum Temp.: 32°F Maximum Temp.: 150°F

IDEAL STORAGE TEMPERATURE
Ideal Storage Temp.: 77°F +/- 5°F Ideal Storage Humidity: 55% +/- 5%

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.

*Contact Your Local BestPack Representative for More Information



LEARN MORE ABOUT OUR TAPE:

BROCHURES | MATERIAL SAFETY DATA SHEET | ROHS INFORMATION

AVAILABLE COLORS:

AVAILABLE LENGTHS:

AVAILABLE WIDTHS:

BP20 (Available in Printed Tape)

**2.0 MIL (50 MICRON) TOTAL TAPE THICKNESS
28 MICRON CAST BOPP LOW ELONGATION FILM
ROHM & HAAS ACRYLIC ADHESIVE**

BP18 is a general purpose utility grade box sealing tape used for primarily light to medium weight boxes. This tape performs well in a broad temperature range.