

# LIGHT TO HEAVY DUTY

## HOT MELT CARTON SEALING TAPE



INSTANT ADHESION  
TO CARTONS

### QUICK HIGHLIGHTS

- Great Initial Tack
- Consistent & Easy Release
- Specially Formulated 140% Elongation Low Stretch Cast Film (Increasing Machine Length Roll Performance)
- Specially Formulated ROHM & HAAS (for use in Hot & Cold Temperature)
- RoHS Compliant
- Meets FDA Food Requirements for Indirect Food Contact

<b>3.0 MIL</b> (76 MICRON)*	<b>60 oz/inch</b> WIDTH***	<b>1.0 MIL</b> (26 MICRON)*
Total Thickness	Peel Adhesion	Adhesive Thickness
<b>2.0 MIL</b> (50 MICRON)*	<b>33 LBS/IN</b> WIDTH**	<b>140%**</b>
Film Thickness	Tensile Strength	Elongation % At Break
Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330		

<b>SERVICE TEMPERATURE</b>
Minimum Temp.: <b>-30°F</b> Maximum Temp.: <b>200°F</b>

<b>USAGE &amp; STORAGE TEMPERATURE</b>
Minimum Temp.: <b>32°F</b> Maximum Temp.: <b>150°F</b>

<b>IDEAL STORAGE TEMPERATURE</b>
Ideal Storage Temp.: <b>77°F +/- 5°F</b> Ideal Storage Humidity: <b>55% +/- 5%</b>

**AVAILABLE COLORS:**    CLEAR

**AVAILABLE LENGTHS:**  50m  100m  150m  914m

**AVAILABLE WIDTHS:**  48mm  72mm  96mm  144mm  288mm

# HT30

**3.0 MIL (76 MICRON) TOTAL TAPE THICKNESS**  
**50 MICRON CAST BOPP LOW ELONGATION FILM**  
**ROHM & HAAS ACRYLIC ADHESIVE**

HT30 is a heavy duty grade carton sealing tape for those applications needing a strong and sturdy seal.



**LEARN MORE ABOUT OUR TAPE:**  
BROCHURES | MATERIAL SAFETY DATA SHEET | ROHS INFORMATION