



MANUAL SIDEDRIVE 2 BOTTOM & 2 TOP SEALER MS2B2T COMPARISON CHART



**WANT TO KNOW MORE
ABOUT THIS MACHINE?**

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.**	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
MS2B2T23-2 2" Tape Head	(39.4") x (36.2") x (68.0")	(6.0" - U) x (10.0" - 21.5) x (5.5" - 30.0")	(20.5" - 30.0")	Up to 40	435	110 Volts 60 Hz	N/A

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.**	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS	AIR REQUIREMENTS
MS2B2T23-2 2" Tape Head	(39.4") x (36.2") x (68.0")	(6.0" - U) x (10.0" - 21.5) x (5.5" - 30.0")	(20.5" - 30.0")	Up to 40	435	110 Volts 60 Hz	N/A
MS2B2T23-3 3" Tape Head	(39.4") x (36.2") x (68.0")	(6.0" - U) x (10.0" - 21.5) x (5.5" - 30.0")	(20.5" - 30.0")	Up to 40	435	110 Volts 60 Hz	N/A

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.
TOP GAP WIDTH RANGE (3.22"-6.5")
BOTTOM GAP WIDTH RANGE (4.0"-6.0")

*OUTSIDE DIMENSIONS ONLY
** BASED ON CUSTOMER APPLICATION
ALL MODELS AVAILABLE IN HIGH SPEED & FOOD GRADE 304 STAINLESS STEEL