



STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS Per Min.***	SHIPPING WEIGHT (LBS)	POWER Requirements
MSAG-3HEB** 3" Tape Head	(58.5") x (43.3") x (65.0")	(6.0" - U) x (8.5" - 31.0") x (6.25" - 20.25")	(20.5" - 30.0")	Up to 35	575	110 Volts 60 Hz

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.***	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS
MSAG-3HEB** 3" Tape Head	(58.5") x (43.3") x (65.0")	(6.0" - U) x (8.5" - 31.0") x (6.25" - 20.25")	(20.5" - 30.0")	Up to 35	575	110 Volts 60 Hz

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

U - UNLIMITED
* OUTSIDE DIMENSIONS ONLY
** HIGH SPEED
*** BASED ON CUSTOMER APPLICATION

WWW.BESTPACK.COM VERSION 4.0_0624