



STAINLESS STEEL MANUAL SIDEDRIVE DUAL MAST MSD-S COMPARISON CHART



**WANT TO KNOW MORE
ABOUT THIS MACHINE?**

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS
MSD22-2S 2" Tape Head	(39.5") x (28.5") x (66.2")	(6.0" - U) x (4.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 40	360	110 Volts 60 Hz

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS
MSD22-2S 2" Tape Head	(39.5") x (28.5") x (66.2")	(6.0" - U) x (4.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 40	360	110 Volts 60 Hz
MSD22-3S 3" Tape Head	(39.5") x (28.5") x (66.2")	(6.0" - U) x (5.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 40	360	110 Volts 60 Hz
MSD23-2S 2" Tape Head	(39.5") x (32.8") x (80.3")	(6.0" - U) x (8.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 40	411	110 Volts 60 Hz
MSD32-2S 2" Tape Head	(39.5") x (43.8") x (70.3")	(6.0" - U) x (4.25" - 20.0") x (3.9" - 30.0")	(25.8" - 30")	Up to 25	432	110 Volts 60 Hz
MSD32-3S 3" Tape Head	(39.5") x (43.8") x (70.3")	(6.0" - U) x (8.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30")	Up to 25	432	110 Volts 60 Hz

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

*OUTSIDE DIMENSIONS ONLY | U - UNLIMITED