

# RANDOM SIDEDRIVE BOTTOM FLAP FOLDER RSBFT COMPARISON CHART



**WANT TO KNOW MORE  
ABOUT THIS MACHINE?**

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

## STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS
RSBFT20-2H** 2" Tape Head	(95.9") x (35.5") x (29.4")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0+)"	(23.5" - 30")	Up to 10	350	110 Volts 60 Hz

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS
RSBFT20-2H** 2" Tape Head	(95.9") x (35.5") x (29.4")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0+)"	(23.5" - 30")	Up to 10	350	110 Volts 60 Hz
RSBFT20-3H** 3" Tape Head	(95.9") x (35.5") x (29.4")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0+)"	(23.5" - 30")	Up to 10	350	110 Volts 60 Hz

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

\*OUTSIDE DIMENSIONS ONLY  
\*\* HIGH SPEED