



BESTPACK



USED FOR SPACING OUT UNIFORM CARTONS
ARX COMPARISON CHART



WANT TO KNOW MORE ABOUT THIS MACHINE?

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	POWER REQUIREMENTS	AIR REQUIREMENTS
ARX20**	(34.2") x (35.0") x (35.0")	(8.0" - 27.5") x (6.0" - 21.0") x (6.0" - 20.0")	(22.5" - 30.0")	110 Volts 60 Hz	50 PSI, 2 SCFM

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	POWER REQUIREMENTS	AIR REQUIREMENTS
ARX10**	(34.2") x (22.5") x (35.0")	(8.0" - 27.5") x (6.0" - 14.6") x (4.5" - 20.0")	(22.5" - 30.0")	110 Volts 60 Hz	50 PSI, 2 SCFM
ARX10H**	(34.2") x (22.5") x (35.0")	(8.0" - 27.5") x (6.0" - 14.6") x (4.5" - 20.0")	(22.5" - 30.0")	110 Volts 60 Hz	50 PSI, 2 SCFM
ARX20**	(34.2") x (35.0") x (35.0")	(8.0" - 27.5") x (6.0" - 21.0") x (6.0" - 20.0")	(22.5" - 30.0")	110 Volts 60 Hz	50 PSI, 2 SCFM
ARX20H**	(34.2") x (35.0") x (35.0")	(8.0" - 27.5") x (6.0" - 21.0") x (6.0" - 20.0")	(22.5" - 30.0")	110 Volts 60 Hz	50 PSI, 2 SCFM

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

** AVAILABLE IN LEFT OR RIGHT ORIENTATION