



Model Shown: PP-1519ECMC

1519EC SERIES

L-BAR SEALER & SHRINK TUNNEL COMBO


Entry-level, Light Duty L- Bar Sealer and Shrink Tunnel Built on the Same Frame.

PRODUCTION
RATE:
up to 8-12 ppm

MAX FILM
WIDTH:
(22.0")

MACHINE DIMENSIONS:
(L x W x H)
(76.0" x 26.0" x 50.0")

SEAL DIMENSIONS:
(L x W)
(19.0" x 15.0")



Specifications based on PP-1519ECMC

This compact Model PP-1519 ECMC L-Sealer with magnetic hold-down and power discharge conveyor and attached tunnel is only 76" in total length. Featuring "Micro Knife" technology - will seal all popular Polyolefin Shrink Films. Tunnel features Live Roller Conveyor with fully Re-Circulating Air Chamber, AC Variable Speed Conveyor, 0-60 FPM, Digital Temperature Control and Automatic Cool Down Shut Off. A great machine for low to medium production speeds of 8-12 packages per minute.

ECONOMY COMBO SERIES

STANDARD FEATURES INCLUDE

L-SEALER FEATURES:

- Seal Dimensions: 15"W x 19"L
- "Micro Knife Technology"
- Easy Load Film Cradle
- Perforating Pin Wheel Hole Punch
- Adjustable Film Loading Tray
- Signals End of Seal Cycle
- Independent Seal and Pulse Timers
- Heavy Duty Stainless Steel Film Clamps
- Production Rates of 8 To 12 PPM

SHRINK TUNNEL FEATURES:

- Heavy Duty "Hi-Density" Roller Spacing
- Anti-Jam Safety Feature In Tunnel
- 2,200 Watt Heaters
- Fully Re-Circulating Air Chamber
- 2,000 RPM Blower Motor
- AC Variable Speed Conveyor
- Digital Tunnel Temperature Control
- Separate Heater Switch
- Automatic Cool Down with Shut Off
- Locking Casters
- 8 Ft Heavy Duty Power Cord

ACCESSORIES:

- Gravity Roller 180° Curved Conveyor with 24" Straight Section



OPTIONS:

- Stainless Steel Frame
- Teflon Mesh Belt Kit in Shrink Tunnel (includes clamp bar)
- Stainless Steel Product Loading Tray

POPULAR ECONOMY COMBO MODELS

MODELS	SEALING DIMENSIONS 15"W x 19"L	POWER REQUIREMENTS 110/220 VOLTS 20 AMPS 1 PHASE	MAX FILM WIDTH 22"
PP-1519EC-110V	L-Sealer/Tunnel Combo		
PP-1519EC-220V	L-Sealer/Tunnel Combo		
PP-1519EC-220V 8"	L-Sealer/Tunnel Combo and 8" Tunnel Opening		
PP-1519ECM-110V	L-Sealer/Tunnel Combo with Magnet Hold Down		
PP-1519ECM-220V	L-Sealer/Tunnel Combo with Magnet Hold Down		
PP-1519ECM-8"-220V	L-Sealer/Tunnel Combo with Magnet Hold Down and 8" Tunnel Opening		
PP-1519ECMC-110V	L-Sealer/Tunnel Combo with Magnet Hold Down and Powered Discharge Conveyor		
PP-1519ECMC-220V	L-Sealer/Tunnel Combo with Magnet Hold Down and Powered Discharge Conveyor		
PP-1519ECMC-8" 220V	L-Sealer/Tunnel Combo with Magnet Hold Down and Powered Discharge Conveyor with 8" Tunnel Opening		

Information subject to change without notice.