



\*Model Shown: PP-5600CS

## 5600CS SERIES

# FULLY AUTOMATIC L-BAR SEALER & TUNNEL

Ideal for Sealing a Wide Variety of Industrial and Consumer Products

PRODUCTION  
RATE:  
**up to 40 ppm**

MAX FILM  
WIDTH:  
**(24.0")**

MACHINE DIMENSIONS:  
(L x W x H)  
**(77.0" x 62.0" x 72.0")**

SEAL DIMENSIONS:  
(L x W x H)  
**(25.0" x 20.0" x 8.0")**



Specifications based on PP-5600CS

Provides a heavy-duty, labor saving option to traditional manual L-bar sealers. Our unique APA (automatic product adjustment) feature makes product size changes a snap. Holds up to 40 package size recipes making changes to time temperature, bag length and conveyor configurations. Many automatic infeed options and the tunnel and sealer come on a common frame.

# FULLY AUTOMATIC L-SEALER & TUNNEL

## STANDARD FEATURES INCLUDE

- “APA” Automatic Product Adjustment
- Vertical Seal Head Design with Center Seal
- Delta 7” Color Touch Screen with 40 Program Memory
- Variable Speed Drive 0-110 FPM
- Delta PLC
- Self-Diagnostics
- Multi-pack option
- Product Staging
- Motorized Scrap Windup with Alarm
- Pinwheel Hole Punch
- Single Piece Hot Knife Seal Bar
- Locking Casters
- 220V, 1 Phase, 20A
- Max Film Width 24”

## OPTIONS:

- Closing Conveyor
- Print Film Registration
- Left to Right Product Flow
- Export Crating
- Non-Standard Voltage
- Pneumatic Hole Punch Single Hole 3/16”
- Dual Pneumatic Hole Punch (Two 3/16” Diameter Holes)
- Poly cord belt infeed conveyor (For easy cleaning)
- 10” Color Touch Screen HMI
- Pressure Roller to Help Move Light Products
- PP-36B 3 ft Belted infeed conveyor
- PP-72B 6 ft Belted infeed conveyor
- PP-36F 3 ft Flighted infeed conveyor
- PP-72F 6 ft Flighted infeed conveyor
- PP-72FB 6 ft Flighted “Bar” Style Infeed Conveyor. (Pushes multiple products at the same time.)
- Pneumatic Product Hold Down for Light Weight Products
- Pneumatic Air Expeller-Helps Evacuate Air from Bag Prior to Sealing
- Short Stroke Cylinder on Seal Head for Increased Speeds of Up to 50 PPM

## POPULAR FULLY AUTOMATIC L-SEALER & TUNNEL MODELS

MODEL	SEALING AREA LENGTH X WIDTH X HEIGHT	MIN PACKAGING SIZE LENGTH X WIDTH X HEIGHT	MAX PACKAGING SIZE LENGTH X WIDTH X HEIGHT	PACKAGES PRE MINUTE
PP5600-COMBO	(25.0" x 20.0" x 8.0")	(2.5" x 2.5" x 0.125")	(24.0" x 16.0" x 8.0")	up to 40
PP5600-COMBO-SS	(25.0" x 20.0" x 8.0")	(2.5" x 2.5" x 0.125")	(24.0" x 16.0" x 8.0")	up to 40

Information subject to change without notice.

SS- Stainless Steel