



*Model Shown: C-Series C-250H


C-SERIES

FLOW WRAPPERS

Great for Wrapping Cookies, Muffins, Candy Bars, Biscuits, Brownies, etc.

PRODUCTION RATE: up to 40-100 ppm	MAX FILM WIDTH: (9.8")	MACHINE DIMENSIONS: (L x W x H) (148.0" x 26.0" x 56.0")	SEAL DIMENSIONS: (L x W x H) (13.0" x 4.2" x 2.0")
--	---	--	--

Specifications based on C-250H



Meet the high-speed side sealing solution that will automate your packing for long products. This solution was built with an intermittent sealing motion with for both speed and economy. Equipped with a sturdy HMI providing the operator with easy to read and adjust operational parameters. The automatic side sealer is equipped with a servo motor allowing for a high-speed design with a sealing capacity of up to 60 packages per minute. The side sealing machine is also equipped with a one-piece, Teflon coated, heat-resistant alloy blade.

AVAILABLE MODELS:

- PP-5545TBH
- PP-5545TBJ-F
- PP-5545TBJ-F

FLOW WRAPPERS

STANDARD FEATURES INCLUDE:

- Mechanical Drive
- Touch Screen Menu with Auto Diagnostics & Error Display
- Product Counter
- 6.5 ft Flighted Infeed Conveyor
- One Step Adjustment of Bag Length
- Print Registration

OPTIONS:

- Teflon Coated Seal Jaws
- Right To Left Product Flow
- Stainless Steel Frame Construction
- Photo Electric Eye (for printed film included)
- All Color Photo Sensor
- Adjustable Film Forming Device
- Additional Fixed Forming Device
- Dual Seal Jaw (standard on C-250H)
- Triple Seal Jaw
- Powered Discharge Wheel on Exit Conveyor
- Gas Flush-Control Valves and Pipes
- Gusseted Bag Device
- Plastic Product Carriers
- Single Head Label Applicator LBL-110 (Label Applicator apply label up to 4.3" x 4.3")
- Dual Head Label Applicator
- Hot Ink Roller Coder
- Hot Ink Ribbon Coder-THR40A
- Elfin 1S Ink Jet Printer (Includes Mounting Hardware)
- Thermal Transfer Ribbon (33mm x 500m or 55mm x 900m)
- Videojet 6330 Thermal Transfer Printer
- Extended Infeed Conveyor-Std Length
- Paper Side Guides on Infeed Decking
- Stainless Steel Infeed Chain
- Hole Punch - Round
- Hole Punch - Euro Slot/Butterfly
- Hole Punch - Tear Notch "V"
- Pin Wheel Hole Punch (one row of pins)
- Stainless Steel Discharge Chute
- End Seal Chain Conveyor
- Manufactured to Meet UL Requirements
- CE Certification
- External Start/Stop Switch (mounted to infeed conveyor)
- No Product-No Cycle function
- Drop Chute
- Right Angle Horizontal Belted Infeed
- Increase Seal Jaw Height of C-350H to 3.1" (80mm)

POPULAR FLOW WRAPPERS MODELS

MODELS	SPEED	SEAL JAW WIDTH	BAG LENGTH	BAG WIDTH	FILM WIDTH	MAX PRODUCT HEIGHT
C250H Single Jaw	(40 to 100ppm)	(4.3")	(3.5" - 13.0")	(1.25" - 4.2")	(3.5" - 9.8")	(2.0")
C250H Dual Jaw	(40 to 125ppm)	(4.3")	(2.9" - 8.6")	(1.25" - 4.2")	(3.5" - 9.8")	(2.0")
C350H Single Jaw	(40 to 100ppm)	(7.0")	(3.5" - 13.0")	(2.0" - 6.25")	(5.0" - 13.75")	(2.5")
C450H Single Jaw	(40 to 100ppm)	(9.0")	(6.3" - 18.9")	(2.2" - 7.8")	(6.0" - 17.5")	(4.0")

Information subject to change without notice.

U - Unlimited