



\*Model Shown: PP-5545TBA

## TBA SERIES

# ENTRY-LEVEL L-BAR SEALERS


Economical solution to production speed and reduce labor costs

**PRODUCTION RATE:**  
up to **40 ppm**

**MAX FILM WIDTH:**  
**(20.0")**

**MACHINE DIMENSIONS:**  
(L x W x H)  
**(71.0" x 40.0" x 66.0")**

**SEAL DIMENSIONS:**  
(L x W x H)  
**(22.0" x 18.0" x 4.75")**



Specifications based on PP-5545TBA

The entry-level automatic L-bar sealer has a large seal area of 22"L x 18"W x 4.75"H and provides an economical, durable and user-friendly solution for those who already have one or two semi-automatic L' Sealers and need to increase production speed and reduce labor costs. The sealing system is capable of performing a smooth and firm seal line for a wide range of products such as toys, cosmetics, tools, food, electric appliances, etc. Use of photo sensors and timers controls the bag length for sealing. Excellent perforation system design allows the pin to be changed easily.

**AVAILABLE MODELS:**

- PP-5545TBA
- PP-5545TBB
- PP-5545TBA + PP-1808-28
- PP-5545TBB + PP-1808-28

# ENTRY-LEVEL L-SEALERS

## STANDARD FEATURES INCLUDE

- Teflon Coated Hot Knife Seal Blade
- Fixed Belt Speed At 65 FPM
- Fast Product Changeovers
- Multiple Pinwheel Hole Punches
- Large Seal Area: 22"L x 18"W x 4.75"H
- Dual Emergency Stop Switches
- Self-Contained Scrap Removal System
- Plexiglas Safety Covers
- Dual Photo-Eye (Horizontal & Vertical)
- Film Miser (Helps Track Film)
- Locking Casters with Leveling Pads
- Max Pkg Size: 20"L x 14.5"W x 4.75"H

## OPTIONS:

- Removable Washdown Infeed Conveyor
- Variable Speed Drive
- Closing Conveyor
- Left To Right Direction
- Photo-Eye For Print Registered Film

## PP-5545TBA L-BAR SEALER & PP-1808-28 SHRINK TUNNEL SET

- The PP-5545TBA/PP1808-28 is a fully automatic L-Sealer and Shrink Tunnel that is sold as a set or individually.



## SHRINK TUNNEL FEATURES:

- Lighted Viewing Window
- Chamber Size 28"L x 18"W x 8"H
- Energy Efficient
- 1/2 HP Blower Motor
- Fully Re-Circulating Air Chamber
- Live Roller Rod Conveyor
- Digital Temperature Controller 0-400°
- 7.5KW Heater Bank
- Variable Speed Drive 0-75 FPM
- Automatic Cool Down and Shut Off
- 220v, 1 Phase, 40 Amp

## POPULAR ENTRY LEVEL L-BAR SEALER MODELS

MODEL	DESCRIPTION	SEALING DIMENSIONS LENGTH X WIDTH X HEIGHT	POWER REQUIREMENTS	MAX FILM WIDTH	PACKAGES PRE MINUTE
PP-5545TBA	L-Bar Sealer	(22.0" x 18.0" x 4.75")	220 Volts 15 Amp 1 Phase	(20.0")	(20.0")
PP-5545TBB	L-Bar Sealer with Closing Conveyor	(22.0" x 18.0" x 4.75")	220 Volts 15 Amp 1 Phase		
PP-5545TBA / PP1808-28	L-Bar Sealer and Shrink Tunnel Set	(22.0" x 18.0" x 4.75")	220 Volts 40 Amp 1 Phase		
PP-5545TBB / PP1808-28	Set with Closing Conveyor	(22.0" x 18.0" x 4.75")	220 Volts 40 Amp 1 Phase		

Information subject to change without notice.