



*Model Shown: PP-5545TBA

TBA SERIES

ENTRY-LEVEL FULLY AUTOMATIC L-BAR SEALERS


Entry-Level Fully Automatic L-Bar Sealer

PRODUCTION
RATE:
up to 40 ppm

MAX FILM
WIDTH:
(20.0")

MACHINE DIMENSIONS:
(L x W x H)
(71.0" x 40.0" x 66.0")

SEAL DIMENSIONS:
(L x W x H)
(22.0" x 18.0" x 4.75")



Specifications based on PP-5545TBA

Provides the most economical solution for simple automation. Easy to learn and easy to use, this fully automatic L-Sealer is a huge labor savings over tradition manual and semi-autic dealers. Stock models include both standard conveyor as well as our very useful closing conveyor for effective small product transfer, Many different sizes of shrink tunnels are available to provide the perfect shrink.

FULLY AUTOMATIC L-SEALERS

STANDARD FEATURES INCLUDE

- Teflon Coated Hot Knife Seal Blade
- Fixed Belt Speed At 65 FPM
- Fast Product Changeovers
- Multiple Pinwheel Hole Punches
- Large Seal Area: 22"L x 18"W x 4.75"H
- Dual Emergency Stop Switches
- Self-Contained Scrap Removal System
- Plexiglas Safety Covers
- Dual Photo-Eye (Horizontal & Vertical)
- Film Miser (Helps Track Film)
- Locking Casters with Leveling Pads
- Max Pkg Size: 20"L x 14.5"W x 4.75"H

OPTIONS:

- Removable Washdown Infeed Conveyor
- Variable Speed Drive
- Closing Conveyor
- Left To Right Direction
- Photo-Eye For Print Registered Film

PP-5545TBA L-BAR SEALER & PP-1808-28 SHRINK TUNNEL SET*

- The PP-5545TBA/PP1808-28 is a fully automatic L-Sealer and Shrink Tunnel that is sold as a set or individually.



SHRINK TUNNEL FEATURES:

- Lighted Viewing Window
- Chamber Size 28"L x 18"W x 8"H
- Energy Efficient
- 1/2 HP Blower Motor
- Fully Re-Circulating Air Chamber
- Live Roller Rod Conveyor
- Digital Temperature Controller 0-400°
- 7.5KW Heater Bank
- Variable Speed Drive 0-75 FPM
- Automatic Cool Down and Shut Off
- 220v, 1 Phase, 40 Amp

POPULAR FULLY AUTOMATIC L-BAR SEALERS MODELS

MODEL	DESCRIPTION	SEALING DIMENSIONS LENGTH X WIDTH X HEIGHT	POWER REQUIREMENTS	MAX FILM WIDTH	PACKAGES PRE MINUTE
PP-5545TBA	L-Bar Sealer	(22.0" x 18.0" x 4.75")	220 Volts 15 Amp 1 Phase	(20.0")	up to 25
PP-5545TBB	L-Bar Sealer with Closing Conveyor	(22.0" x 18.0" x 4.75")	220 Volts 15 Amp 1 Phase	(20.0")	up to 25
PP-5545TBA-SS	Stainless Steel L-Bar Sealer	(22.0" x 18.0" x 4.75")	220 Volts 15 Amp 1 Phase	(20.0")	up to 25
PP-6560TBA	L-Bar Sealer	(25.0" x 23.5" x 5.0")	220 Volts 15 Amp 1 Phase	(26.0")	up to 25
PP-5545TBA / PP1808-28	L-Bar Sealer and Shrink Tunnel Set	(22.0" x 18.0" x 4.75")	220 Volts 40 Amp 1 Phase	(20.0")	up to 25
PP-5545TBB / PP1808-28	Set with Closing Conveyor	(22.0" x 18.0" x 4.75")	220 Volts 40 Amp 1 Phase	(20.0")	up to 25

Information subject to change without notice.