

\*Model Shown: PP-5545TBH

## TBH SERIES

# INTERMITTENT MOTION SIDE SEALER


High Speed Shrink Wrapper for Packaging a Wide Variety of Products.

PRODUCTION  
RATE:  
**up to 60 ppm**

MAX FILM  
WIDTH:  
**(25.0")**

MACHINE DIMENSIONS:  
(L x W x H)  
**(82.7" x 58.3" x 51.5")**

SEAL DIMENSIONS:  
Cross Seal x Height  
**(18.0" x 6.0")**



Specifications based on PP-5545TBH

2-Belt fully automatic, infinite length, side seal machines will seal all commercially available polyolefin and polyethylene films. 2-belt design provides for smooth product transition from infeed belt to side seal, then through cross seal bar.

# INTERMITTENT MOTION SIDE SEALER

## STANDARD FEATURES INCLUDE

- Omron PLC
- Teflon Coated Hot Knife Cross Seal Bar
- Servo Motor Drive on Cross Seal
- Independent Digital Temperature Controls
- Omron Color Touch Screen
- Motorized Scrap Wind Up Wheel with Built In Alarm When Full
- Emergency Stop Switch with Reset Button
- Automatic Pin Wheel Hole Punch
- Powered In-Feed Conveyor with Electric Eye to Start Cycle
- Adjustments for Bag Size Front And Back
- Rear Mounted Film Carriage
- Accepts Random Length Products, No Changeover Required
- Adjustable Height Legs with Locking Casters
- Fully Enclosed Seal Area
- Safety Interlocks on All Doors
- Air Required 3-4 CFM at 80 PSI
- Omron Inverter Drives With Variable Speed Drive 0 To 100 FPM

## OPTIONS:

- Closing Conveyor to Transfer Small Package Sizes

## POPULAR INTERMITTENT MOTION SIDE SEALER MODELS

MODEL	SEALING DIMENSIONS CROSS SEAL X HEIGHT	POWER REQUIREMENTS	MAX PACKAGE SIZE WIDTH X HEIGHT	MAX FILM WIDTH	PACKAGES PRE MINUTE
PP-5545TBH	(18.0" x 6.0")	220V, 1 Phase, 15A	(15.0" x 6.0")	(25.0")	up to 60
PP-5560TBH	(24.0" x 6.0")	220V, 1 Phase, 20A	(20.0" x 6.0")	(33.0")	up to 50
PP-5580TBH	(31.0" x 12.0")	220V, 3 Phase, 25A	(24.0" x 12.0")	(39.0")	up to 50

Information subject to change without notice.