



CARTON SEALING SOLUTION

EQUPPIED WITH

EXTENDED BELT DRIVES

& TOP FLAP FOLDERS

QUICK HIGHLIGHTS

SEALS UP TO 40 CARTONS PER/MIN.*

- Entry Level Automation Solution that Pairs Wells with a Packing Station
- Manually Adjust Height and Width of Carton Sealer for Each Carton Size
- Reduced Repetitive Motion for Operator Due to the Extended Belt Drives & 3 Flap Folders
- Mounting of Electrical Box or Handles on Either Side



Specifications based on MSD22-2EE

Length (min. - max.) (6.0" - U)

Width (min. - max.) (4.25" - 20.0")

Height (min. - max.) (3.38" - 20.5")









BONUS 2-YEAR

SA BPA MEM

FREE PRODUCT SUPPORT:

TRAINING VIDEOS | ONLINE MANUALS | TECH SUPPORT

*CONTACT YOUR LOCAL BESTPACK REPRESENTATIVE FOR MORE INFORMATION WWW.BESTPACK.COM

MSD-EB

MANUAL SIDEDRIVE W/EXTENDED BELT DRIVES

The BestPack™ MSD-EB sealer is a unique multi-purpose solution. Featuring a convenient top 3-flap folder and extended side-drive system, the MSD-EB enables a person to efficiently erect, pack, flap fold, and seal a carton in one station. Dual telescopic masts allow for an extra 4" carton height extension on the upper assembly and two 110V UL-approved electric motors power the extended side belt drive.

VERSION 2.0_0324



UNIFORM TOP FLAP FOLDEREliminates repetitive manual folding of flaps



DUAL TELESCOPING MASTStronger design, capable of precise adjustments resulting in a clean, consistent seal.



EXTENDED SIDEBELT DRIVE SYSTEMGently pulls product through while reducing less wear & tear on parts.



TOP COMPRESSION ROLLERSEliminates the carton's top gap for added product security.



COMPLETE BED ROLLER SYSTEM Increase throughput while reducing strain on the motor.



ACCESSIBLE TECHNICAL SUPPORTConvenient technical support is readily available via a QR code on solution.

MACHINE FOOTPRINT Specifications based on MSD22-2EB William Specifications based on MSD22-2EB Note: Dimensions are all subject to change without prior notification.

OPTIONS

- Available in Stainless Steel
- Additional Safety Options
 Interlock Safety Gates
- Low-Tape/No-Tape Monitoring
- Infeed/Exit Conveyors
- Heavy Duty Casters
- High-Speed Options (Up to 125 ft. per min.)

POPULAR MSD-EB MODELS

PLEASE REFER TO COMPARISON CHART FOR COMPLETE LIST OF MODELS.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS
MSD22-2EB 2" Tape Head	(59.0") x (32.8") x (59.6")	(6.0" - U) x (4.25" - 20.0") x (3.38" - 20.5")	(23.5" - 30")	Up to 40	492	110 Volts 60 Hz
MSD22-3EB 3" Tape Head	(59.0") × (32.8") × (59.6")	(6.0" - U) x (5.25" - 20.0") x (3.38" - 20.5")	(23.5" - 30")	Up to 40	492	110 Volts 60 Hz

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

*OUTSIDE DIMENSIONS ONLY U - UNLIMITED ALL MODELS AVAILABLE IN HIGH SPEED & FOOD GRADE 304 STAINLESS STEEL

