



MANUAL SIDEDRIVE W/EXTENDED BELTS MSDEB COMPARISON CHART



**WANT TO KNOW MORE
ABOUT THIS MACHINE?**

SCAN HERE TO LEARN MORE ABOUT THIS MACHINE

STANDARD MODEL INFORMATION:

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS
MSD22-2EB 2" Tape Head	(59.0") x (32.8") x (59.6")	(6.0" - U) x (4.25" - 20.0") x (3.38" - 20.5")	(23.5" - 30")	Up to 40	492	110 Volts 60 Hz

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)	POWER REQUIREMENTS
MSD22-2EB 2" Tape Head	(59.0") x (32.8") x (59.6")	(6.0" - U) x (4.25" - 20.0") x (3.38" - 20.5")	(23.5" - 30")	Up to 40	492	110 Volts 60 Hz
MSD22-3EB 3" Tape Head	(59.0") x (32.8") x (59.6")	(6.0" - U) x (5.25" - 20.0") x (3.38" - 20.5")	(23.5" - 30")	Up to 40	492	110 Volts 60 Hz

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE.

*OUTSIDE DIMENSIONS ONLY
U - UNLIMITED

ALL MODELS AVAILABLE IN HIGH SPEED & FOOD GRADE 304 STAINLESS STEEL