



Fully Automatic, 250% Powered Pre-Stretch

construction: **Standard Duty**

TURNTABLE RPM: **0-12**

WARRANTY:

1 Year



Specifications based on PP-4505A-2

Our most advanced machine designed to streamline the packaging process for palletized goods. It automatically wraps stretch film around pallets, ensuring secure and stable loads for storage and transportation.

AVAILABLE MODELS:

- PP-4505A-2
- PP-4505ASP-2

AUTOMATIC PALLET WRAPPERS

STANDARD FEATURES INCLUDE:

- Wireless remote control
- HMI control touch panel
- Independent film tension control
- Heavy duty drive chain for film carriage
- AC motor invertors with PLC control system
- Photo Eye
- Soft start and stop
- Emergency Stop Switch
- Film core diameter is 3"
- Max film roll diameter is 9.8"
- Variable Speed Turntable 0 to 12 RPM
- Turntable diameter of 65"

- Height of turntable 4.3"
- Production Rate: 30 to 40 loads per hour
- 4,400 Lbs load capacity
- Max load size 40" x 48" x 85"
- Maximum Diagonal 61.5"
- Automatic "Cut and Clamp" attach to the load
- Automatic "Cut and Wipe"
- Forklift Portable (Front or Back)

OPTIONS:

- Standard Ramp 59"
- Longer Ramp 79"
- Ramp for Scale Models

- All Black Photo Eyes (able to read dark or black pallet loads)
- 102" Tall Mast for Wrapping High Pallet Loads
- 118" Tall Mast for Wrapping High Pallet Loads

POPULAR AUTOMATIC PALLET WRAPPER MODELS

MODELS	DESCRIPTION	PRODUCTION Rate	MAX LOAD SIZE (LENGTH X WIDTH X HEIGHT)	MAXIMUM Load Size	POWER REQUIREMENTS
PP-4505A-2	Cut, Clamp & Wipe Low Profile	30-40 loads per hour	(40.0" x 48.0" x 85.0")	4,400 lbs	110 Volts, 1 Phase, 15 Amp
PP-4505A-2-SCALE	Cut, Clamp & Wipe Low Profile w/ Scale				

Information subject to change without notice.

