

Model Shown: PP-1606-20

16" SERIES

LIGHT DUTY HEAT SHRINK TUNNELS


Can be used with a wide variety of applications

TEMPERATURE:
0-310°F

POWER
2 KW

FLOW:
Top Down

WARRANTY:
2 Years



Specifications based on PP-1606-20

The General Purpose, Entry Level Heat Shrink Tunnel which can be used for a wide variety of applications such as laying bottles down and using full length PVC shrink sleeves, shrinking pre-form shrink bands over containers, using regular cut shrink bands, can be used as a curing tunnel or a drying tunnel.

AVAILABLE MODELS:

- PP-1606-20 110V/220V
- PP-1608-20 220V

LIGHT DUTY SHRINK TUNNELS

STANDARD FEATURES INCLUDE

- Fully Re-Circulating Shrink Tunnel
- 4 Direction Air Flow
- AC Variable Speed Conveyor 0-75 FPM
- Live Roller Rod Conveyor
- Automatic Cool Down and Shut Off
- Digital Temperature Control 0-310°
- Hi Density Rollers with Close Spacing
- Legs & Locking Casters
- 12ft Power Cord

POPULAR LIGHT DUTY SHRINK TUNNEL MODELS

| MODELS | CHAMBER SIZE (LENGTH X WIDTH X HEIGHT) | MACHINE DIMENSIONS (LENGTH X WIDTH X HEIGHT) | POWER REQUIREMENTS | WEIGHT |
|-----------------|---|---|---------------------------|-----------------|
| PP-1606-20 110V | (20.0" x 16.0" x 6.0") | (35.5" x 22.0" x 48.5") | 110 Volts 20 AMPS 1 Phase | 220 lbs (100kg) |
| PP-1606-20 220V | (20.0" x 16.0" x 6.0") | | 220 Volts 10 AMPS 1 Phase | |
| PP-1608-20 220V | (20.0" x 16.0" x 8.0") | | 220 Volts 10 AMPS 1 Phase | |

Information subject to change without notice.